



EG901



FEATURES

- ▶ Wide and deep tread for highway use with an outstanding wear resistance and durability
- ▶ Sturdy blocks is optimized for all season traction & braking
- ▶ Wide and deep tread enhances the cost per mileage
- ▶ The discontinuity of center rib prevents it from rupturing

Size	PR	LI/SS	Type	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Load		Pressure	
								S(kg)	D(kg)	S(kPa)	D(kPa)
10.00R20	18	149/146L	T/T	7.50	1054	278	15	3250	3000	930	930
11.00R20	18	152/149K	T/T	8.00	1085	293	16.5	3550	3250	930	930
12.00R20	18	154/151K	T/T	8.50	1125	315	16.5	3750	3450	830	830
11R22.5	16	146/143L	T/L	8.25	1054	279	16	3000	2725	830	830
12R22.5	16	150/147L	T/L	9.00	1085	300	18	3350	3075	830	830
13R22.5	18	154/151K	T/L	9.75	1124	320	18	3750	3450	830	830
315/80R22.5	18	154/151L	T/L	9.00	1076	312	17	3750	3450	830	830
315/80R22.5	20	156/153L	T/L	9.00	1082	312	18.5	4000	3650	850	850

